

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : A61B 17/60	A1	(11) International Publication Number: WO 98/36698 (43) International Publication Date: 27 August 1998 (27.08.98)
(21) International Application Number: PCT/US98/03509 (22) International Filing Date: 23 February 1998 (23.02.98) (30) Priority Data: 08/803,805 22 February 1997 (22.02.97) US (71)(72) Applicant and Inventor: SLOCUM, D., Barclay [US/US]; 34235 Van Duyn Road, Eugene, OR 97408 (US). (74) Agents: KOLISCH, J., Pierre et al.; Kolisch, Hartwell, Dickinson, McCormack & Heuser, Suite 200, 520 S.W. Yamhill Street, Portland, OR 97204 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: JOINT SUPPORT

(57) Abstract

A joint support (10) is attachable to a limb of an animal to limit movement of an associated limb joint substantially about a single axis. The joint support includes a radial element (18) having a longitudinal axis and a transverse element (32) having a longitudinal axis. The transverse element (32) is pivotally connected to the radial element (18) about an axis of rotation. The longitudinal axis of the radial element (18) substantially intersects with the axis of rotation, and radial rotation of the radial element (18) is restricted about the axis of rotation. The longitudinal axis of the transverse element (32) is partially fixed relative to the radial element (18) so that the same is substantially co-planar with the longitudinal axis of the radial (18), element and substantially offset from the axis of rotation.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## JOINT SUPPORT

### Cross-Reference to Related Applications

This application claims priority from U.S. Provisional Patent Application Serial No. 60/012,187 entitled "JOINT SUPPORT" filed on February 23, 1996.

### Technical Field

The invention relates generally to devices for supporting a joint in the limb of an animal, such as the joint between the tibia and the tarsus. The invention is attachable to desired bones of the animal via bone pins that penetrate the bone and extend through the animal flesh. Put another way, the joint support of the present invention is an external bone-joint fixator. The joint support has certain adjustable features, but once it is placed in an adjusted position, the joint support has a single degree of freedom about a hinge. When attached to pre-selected bones of an animal so that the hinge overlies a joint located between the bones, the joint support limits movement of that joint to the single degree of freedom of the support.

### Background Art

It is known to attach an external, mechanically hinged joint brace to a human limb, with the hinge overlying a joint in that limb. For example, U.S. Patent No. 5,376,091 discloses several such braces. Another such conventional brace is known as the Richards-Ilizarov System.

However, conventional joint braces have been constructed only for application to human joints. Such joint braces are ineffective for application to animals, at least in part because they are too complicated, and thus likely to be damaged or otherwise disturbed by the animal while wearing the brace. Conventional joint braces are also structurally inadequate for joints in animal limbs.

### Summary of the Invention

The present invention provides a joint support that effectively supports the joints of animals, and is particularly suited for use with domesticated animals such as dogs and cats. The invention generally includes a hinge, a radial support element attached to one side of the hinge, and a transverse support element attached to the other side of the hinge. The transverse element rotates relative to the radial element, with the transverse element rotating tangentially about the hinge. Tangential rotation means that the axial portion of the transverse element closest to the axis of rotation of the hinge defines substantially a circle as it rotates around the hinge, and the longitudinal axis of the transverse element is about tangent to the defined circle.

In the preferred embodiment, the hinge includes what is referred to as a radial block and a transverse block, with the radial block being that portion of the hinge that is attached to the

In the preferred embodiment, the hinge includes what is referred to as a radial block and a transverse block, with the radial block being that portion of the hinge that is attached to the radial support element, and the transverse block being that portion of the hinge that is attached to the transverse support element. The radial support element is fixed to the radial block, and the transverse support element extends through the transverse block to define an anterior portion and a posterior portion of the transverse element. In one embodiment of the present invention, the transverse element is releasably retained within the transverse block by a setscrew so that the proportion of the length of the anterior portion to the length of the posterior portion can be adjusted as necessary. Alternatively, the transverse element can be permanently affixed to the transverse block. In either embodiment, both the transverse and radial elements can be cut to any desired length.

#### Brief Description of the Drawings

Fig. 1 is a top view of the present invention, showing the support elements and hinge, but exclusive of attached bone pins and clamps;

Fig. 2 is a side elevation of the joint support shown in Fig. 1, illustrating in schematic form the attached bone pins;

Fig. 3 is a bottom view of the joint support shown in Fig. 2;

Fig. 4 is a cross-sectional view of the joint support shown in Fig. 2, taken generally along line 4-4 in Fig. 2, and omitting attached bone pins;

Fig. 5 is a cross-sectional view of the joint support shown in Fig. 4, taken generally along line 5-5 in Fig. 4;

Fig. 6 is a cross-sectional of an alternative embodiment of the joint support shown in Fig. 4, taken generally along line 6-6 in Fig. 4, showing a alternate method of attaching the support elements to the hinge blocks, and shown with sections of the transverse support element removed; and

Fig. 7 is a medial view of a section of a dog skeleton, showing the tibia, tarsus and metatarsus attached to the joint support of the present invention.

#### Detailed Description of the Drawings and

#### Best Mode for Carrying Out the Invention

Referring generally to the drawings and focusing particularly on Fig. 2, a joint support according to the present invention is indicated generally at 10. Joint support 10 includes a

hinge 12 defined by a pintle 14, preferably with a tubular passage 15 being formed in pintle 14 to define a longitudinal axis or hinge axis 16. Hinge 12 can be further defined to include a pair of hinge bodies.

One such hinge body is a radial block 18, having a tongue 20 in which is formed a pintle bore 22 defining a longitudinal axis 24. Radial block 18 further includes a body 26 in which is formed a radial bore 28 defining a longitudinal axis 30. Radial bore axis 30 is preferably substantially perpendicular to and intersecting pintle bore axis 24.

Another such block is a transverse block 32, having a tongue 34 in which is formed a pintle bore 36 defining a longitudinal axis 38. Transverse block 32 further includes a body 40 in which is formed a transverse bore 42 defining a longitudinal axis 44. Transverse bore axis 44 is preferably substantially perpendicular to and offset from pintle bore axis 38. A setscrew bore 46 extends through transverse block 32 to open into transverse bore 42, and is preferably substantially perpendicular to the transverse bore.

Joint support 10 includes support structure 48 operatively connected to hinge 12. One element of support structure 48 is a radial element 50 defining a longitudinal axis 52. Radial element 50 is connected to hinge 12 so that radial axis 52 is substantially perpendicular to and intersecting hinge axis 16. Another element of support structure 48 is a transverse element 54, defining a longitudinal axis 56, and in combination with radial element 50, defining a plane of support. Transverse element 54 includes an anterior portion 58 and a posterior portion 60, with anterior portion 58 being defined relative to posterior portion 60 by a line that extends perpendicularly from radial element 50 and intersects pintle bore axis 24. Longitudinal axis 56 is substantially perpendicular to and offset from hinge axis 16.

In the preferred embodiment, radial element 50 extends into radial bore 28, and transverse element 54 extends through transverse bore 42. Radial element 50 is fixed to hinge 12, preferably by threading radial element 50 into bore 28. The threaded engagement provides a relatively secure attachment, particularly when joint 10 is attached to an animal, yet also allows easy substitution of one length of radial element 50 for another.

Other methods of attaching radial element 50 to hinge 12 could be used, including pressing, gluing, brazing or welding radial element 50 into hinge 12. Alternatively, radial element 50 could be fixed relative to hinge 12 by a setscrew, not shown, or element 50 could be formed with an integral pintle bore, also not shown. Transverse element 54 is fixed relative to hinge 12 by

a setscrew 62, having a tool socket 64 and defining a longitudinal axis 66. As with radial element 50, transverse element 54 could be threaded into transverse block 32, or formed with an integral pintle bore, not shown. Other means of pivotally interconnecting radial element 50 to transverse element 54, while preserving the relationship of elements 50 and 54 to the defined axis of pivoting are intended to be within the scope of the claims, set forth below.

For reference, bone pins are indicated generally at 68, each defining a longitudinal axis 70 that is usually substantially normal to the support plane defined by support structure 48. Joint support 10 can be used with other configurations of bone pins 68. Bone pins 68 are attached to support structure 48 as desired, with clamps 72 as shown in Figs. 2-3.

Fig. 7 shows a representative example of joint support 10 being used to support the hock joint of a dog. Pertinent sections of a dog anatomy are shown generally at 100, including a tibia, a tarsus and a metatarsus.

#### Industrial Applicability

The joint support of the present invention is applicable in any situation where it is desired to support a movable joint of an animal. It is particularly applicable to the support of the tibia-tarsal joint (hock joint) and the humerus-ulna/radius joint (elbow joint) of a dog or a cat.

## I CLAIM:

1. A joint support for attachment to a limb of an animal, thereby limiting the movement of a joint in that limb to be substantially around a single axis, the joint support comprising:

a radial element having a longitudinal axis;

a transverse element having a longitudinal axis, the transverse element operatively, pivotally connected to the radial element around an axis of rotation; and

wherein the longitudinal axis of the radial element substantially intersects with the axis of rotation, and the radial element is restricted to about radial rotation about the axis of rotation, and wherein the longitudinal axis of the transverse element is partially fixed relative to the radial element to be substantially coplanar but not collinear with the longitudinal axis of the radial element, and to be substantially offset from the axis of rotation.

2. The joint support according to paragraph 1, wherein the longitudinal axis of the transverse element is substantially perpendicular to the axis of rotation so that the transverse element is restricted to about tangential rotation around the axis of rotation.

3. A joint support for attachment to a limb of an animal, the joint support limiting the movement of a joint in that limb to be substantially around a single axis, the joint support comprising:

a hinge having two connected hinge blocks that pivot around a predefined hinge axis;

a radial element having a longitudinal axis, the radial element attached to one of the hinge blocks so that the longitudinal axis of the radial element is substantially perpendicular to the hinge axis, and so that the longitudinal axis of the radial element substantially intersects with the hinge axis, wherein the radial element is restricted to radial rotation around the hinge axis; and

a transverse element having a longitudinal axis, the transverse element operatively connected to another of the hinge blocks so that the longitudinal axis of the transverse element is substantially offset from the hinge axis.

4. The joint support according to paragraph 3, wherein the longitudinal axis of the transverse element is substantially perpendicular to the axis of rotation so that the transverse element is restricted to about tangential rotation around the hinge axis.



5. A joint support for supporting the tarsus and metatarsus of an animal relative to the tibia, the joint support comprising:

a pintle having a longitudinal axis;

a radial block having formed therein a pintle bore, the pintle bore including a longitudinal axis, wherein the radial block is mounted on the pintle;

a transverse block having formed therein a pintle bore, the pintle bore having a longitudinal axis, wherein the transverse block is mounted on the pintle;

a radial element having a longitudinal axis, the radial element operatively connected to the radial block so that the longitudinal axis of the radial element is substantially perpendicular to the longitudinal axis of the pintle, and so that the longitudinal axis of the radial element substantially intersects the longitudinal axis of the pintle; and

a transverse element having a longitudinal axis, the transverse element operatively connected to and extending through the transverse block to define an anterior portion and a posterior portion of the transverse element, with the longitudinal axis of the transverse element being substantially offset from the longitudinal axis of the pintle and substantially coplanar with the longitudinal axis of the radial element;

wherein, in use, the radial element is affixed to the tibia and the transverse element is affixed to the tarsus and metatarsus, with the posterior portion of the transverse element being generally affixed to the tarsus and the anterior portion of the transverse element being generally affixed to the metatarsus.

6. The joint support according to paragraph 5, wherein the longitudinal axis of the transverse element is substantially perpendicular to the axis of rotation so that the transverse element is restricted to about tangential rotation around the longitudinal axis of the pintle.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6



# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US98/03509

<b>A. CLASSIFICATION OF SUBJECT MATTER</b> IPC(6) : A61B 17/60 US CL : 606/54 According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) U.S. : 606/54-59 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched none Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) none		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4,604,997 A (DE BASTIANI et al.) 12 August 1986, entire reference.	1
A	US 4,922,892 A (AGEE et al.) 08 May 1990, entire reference.	1
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* Special categories of cited documents: *A* document defining the general state of the art which is not considered to be of particular relevance *E* earlier document published on or after the international filing date *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) *O* document referring to an oral disclosure, use, exhibition or other means *P* document published prior to the international filing date but later than the priority date claimed *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art *Z* document member of the same patent family		
Date of the actual completion of the international search 19 JUNE 1998		Date of mailing of the international search report 14 JUL 1998
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230		Authorized officer <i>Guy V. Tucker</i> GUY V. TUCKER Telephone No. (703) 308-3271

THIS PAGE BLANK (USPTO)